

Exhibit A

UDO Amendment #1 – Appendix M: FEMA Flood Insurance Study Maps and Profiles (page 41)

See attached Appendix M

UDO Amendment #2 – Article 14 – Definition of NAVD (page 14-36)

	NAVD 88	North American Vertical Datum of 1988. Supersedes NGVD29, effective September 18, 2013.
	NGVD	National Geodetic Vertical Datum of 1929. Superseded by NAVD 88, effective September 18, 2013.

UDO Amendment #3 – Appendix S (page 90)

Appendix S: UDO MITIGATION REQUIREMENTS AND GUIDELINES FOR ISOLATED WATERS OF LAKE COUNTY IMPACTS

- c. Hydrology Monitoring: A sufficient number of representative sample points shall be established in each mitigation wetland to assess the hydrologic conditions. The sample points shall be monumented in the field with a metal stake. The location of each sample point shall be accurately identified on the Planting Plan (Appendix S, Section C.4.), which shall be included in the annual monitoring reports. At a minimum, hydrology monitoring shall be conducted on a bi-weekly basis during the first growing season and on a monthly basis during each succeeding growing season of the monitoring period. Hydrology sampling shall include the following, at a minimum:

- 1) Depth of inundation [\(in. or cm.\) based on ~~in~~ NAVD 88 datum, which supersedes the NGVD29 datum used prior to September 18, 2013](#)~~NGVD as amended 1929 (in. or cm.), and~~
-

UDO Amendment #4 – Article 8, Section 8.1.6.2.e.1.a (page 8-12)

- a) Existing contour lines at not greater than 1 foot intervals. The reference bench mark shall be cited on the plan. Spot elevations shall be provided at all breaks in grade and where necessary to indicate grade changes in areas of shallow topography. The source and/or preparer of the topographic survey shall be recognized on the plan. All elevations shall be referenced to [North American Vertical Datum of 1988 \(NAVD 88\), which supersedes the NGVD29 datum used prior to September 18, 2013](#)~~National Geodetic Vertical Datum (NGVD) (1929 adjusted)~~, and [Revised 10.09.12]
-

UDO Amendment #5 – Article 10, Section 10.9.5.4.c.3.a (page 10-34)

- a) existing contour lines at not greater than 1 foot intervals extending a minimum of 200 feet off-site. All elevations shall be referenced to [North American Vertical Datum of 1988 \(NAVD 88\), which supersedes the NGVD29 datum used prior to September 18, 2013](#)~~National Geodetic Vertical Datum (NGVD), 1929 adjusted~~;
-

UDO Amendment #6 – Article 10, Section 10.17.1 (page 10-62)

All federal, state, county or official bench marks, monuments or triangulation stations in or adjacent to the subdivision shall be preserved. Before moving any bench mark, monument or triangulation station, the authority having jurisdiction over the monument shall be notified and given sufficient time to take appropriate action. All elevations shall be referred to [North American Vertical Datum of 1988 \(NAVD 88\), which supersedes the NGVD29 datum used prior to September 18, 2013](#)~~National Geodetic Vertical Datum, 1929 adjusted~~.
